

CAST IRON FOOT VALVE

Flange dimensions and holes according to:

UNE-EN 1092-2 PN10.



DNS-PN16-56-FV

CONSTRUCTION

Nº	NAME	MATERIAL	QTY.	NORM
1	STRAINER (1)	Steel / polypropylene	1	-
2	SEALING VALVE	Cast iron	1	EN-GJL-250 GG-25
3	SPINDLE	Stainless steel	1	AISI 420
4	BODY	Cast iron	1	EN-GJL-250 GG-25
5	SPRING	Stainless steel	1	AISI 304
6	SEALING JOINT	Rubber	1	-
7	SEALING RING	Cast iron	1	EN-GJL-250 GG-25

(1) Size Ø80 and Ø200 in steel plate construction.
Size Ø100, Ø125 and Ø150 in polypropylene construction.

OPTIONS

- Especial flange for bores with vertical pumps (FIG.54).
- With sealing joint in NBR / EPDM.
- In Stainless Steel AISI 304 strainer construction.



With especial flange



With stainless steel AISI 304 strainer construction

CAST IRON FOOT VALVE

DIMENSIONS

Size	H	ØD (PN10)	ØK (PN10)	n° x d (PN10)	Weight Kg
80	230	200	160	8 x 19	8
100	295	220	180	8 x 19	13
125	335	250	210	8 x 19	19
150	335	285	240	8 x 23	24
200	430	340	295	8 x 23	40

Measures in mm.

DIMENSIONS

Size	H	ØD (Especial flange)	ØK (Especial flange)	n° x d (Especial flange)	Weight Kg
80	230	140	125	4 x 9.5	6
100	295	180	155	4 x 15	9
125	335	215	185	8 x 15	14
150	335	240	210	8 x 18	17
200	430	290	260	8 x 18	31

Measures in mm.

Nº	NAME
1	STRAINER
2	SEALING VALVE
3	SPINDLE
4	BODY
5	SPRING
6	SEALING JOINT
7	SEALING RING

